

SPINNE



• Magnetized pin media provides unmatched finish quality

(SPINner

- Deburrs where hand deburring cannot
- Great for irregular parts and small precision parts

SEND US YOUR PARTS FOR FREE TESTING. SEE THE SPINNER WORK FOR YOU!



Our deburring specialist will provide a complete report. Includes specific media used & average deburring time. **Techniks Inc. 9930 E. 56th St. Indianapolis, IN 46236**



Techniks is a proud member of Techniks Tool Group. CNC TOOLING SOLUTIONS FROM SPINDLE TO WORKPIECE

ELIMINATE

TIME-CONSUMING

DEBURRING

FINISHING & POLISHING

Techniks Inc. 9930 E. 56th St. Indianapolis, IN 46236 | 800.597.3921 | www.techniksusa.com | info@techniksusa.com

SPINNER FEATURES & APPLICATION EXAMPLES

SPINNER KEY POINTS:

- Deburring is fast and media will not harm part or affect tolerances
- sPINner media lasts 3-5 years and is safe to handle during operation
- Parts separator available for high volume needs
- Does not transfer material, will not introduce new particles to your parts

APPLICATIONS INCLUDE:

- Surface polishing
- Pre-electroplating processing
- Removing heat treat scaling
- Oxidized grease/film cleaning
- Removing rust/cleaning threads

CASE-STUDY EXAMPLES





BEFORE



slots

drill holes

threads

cross holes

internal

threads

internal cavities





Dimensions	4.75" x 2.125" x 2.75"
Problem	Soft material with long burrs left in multiple thin slits and rough edges.
Deburring Time	15 minutes.

Case 3: Stainless Steel Turned & Machined Part

Dimensions	3/4" diameter x 1 7/16" long				
Problem	Rusty compact cylinder with burrs left in multiple cross-drilled holes.				
Deburring Time	20 minutes.				





1.25"

3″





2

SPINNER OPERATION GUIDE



HOW THE SPINNER WORKS

- Powerful magnet located below the sPINner body well creates a rotating magnetic field, stirring the contents within your sPINner tub
- The tumbling action of the magnetized stainless steel pin media effectively deburrs, smooths rough edges, and polishes your parts for the highest quality finish possible

OPERATION PROCEDURE

- Choose the container based on the amount and size of your parts
- Place a single layer of your parts on the bottom of the container, make sure your parts are not overlapping
- Mix water & deburring solution for a 50:1 water to solution ratio. (Add more solution for brighter, shiny parts.)
- Secure lid to container
- Enter cycle time, adjust speed / intensity, and press START (Note: cycle time, media size, and parts quantity will depend on your application.)

PARTS & MEDIA SEPARATION PROCEDURE

- Slowly drain water/solution leaving parts and media
- Place media and parts into the separation container
- Turn the spin frequency to about 1/2 power. Run machine for about 10 seconds
- Stop the machine. Your parts should be trapped in the top of the separation container. The pins will be pulled through the separation container to the bottom. (Repeat until media and parts are fully separated.)









SPINNER MACHINES AND MEDIA





MACHINES INCLUDE:

- Deburring container
- PFS-747 deburring solution
- Media separator sieve Choose media specific to your parts. (see below)

Machine No.	LxWxH	Tank Size L x W	Container W x H	Power Supply	Amps	Weight	Media needed for full charge
EHD-728	19" x 19" x 37"	11" x 11"	9" x 8"	220V single phase	5	160 lbs.	1 kg.
EHD-735	23" x 26" x 34"	15" x 16"	13" x 9"	220V single phase	10	220 lbs.	3 kgs.
EHD-750	29" x 30" x 36"	21" x 23"	19" x 10"	220V single phase	15	385 lbs.	4 kgs.
EHD-765	37" x 39" x 43"	29" x 26.75"	25" x 10"	220V single phase	10	516 lbs.	6 kgs.
EHD-7200	58" x 26.5" 43"	50" x 14"	32" x 12"	220V three phase	15	1,100 lbs.	-
ESS-660	18" x 18" x 26"	18" x 18"	N/A	110V/220V	15	97 lbs.	-

SPINNER MEDIA:	Pin No.	Dia. x Length	Pin No.	Dia. x Length	Pin No.	Dia. x Length
	EHD-S1	0.2mm x 5mm	EHD-P5	0.7mm x 3mm	EHD-P10	1.2mm x 3mm
	EHD-P1	0.3mm x 3mm	EHD-S5	0.7mm x 5mm	EHD-S8	1.2mm x 5mm
	EHD-S2	0.3mm x 5mm	EHD-P6	0.8mm x 3mm	EHD-P42	1.2mm x 10mm
	EHD-S13	0.3mm x 7mm	EHD-S6	0.8mm x 5mm	EHD-P9	1.5mm x 3mm
• SUS 304 stainless steel pins	EHD-P2	0.4mm x 3mm	EHD-P7	1.0mm x 1mm	EHD-S9	1.5mm x 5mm
Hardened to HRC 30	EHD-S3	0.4mm x 5mm	EHD-P8	1.0mm x 3mm	EHD-A3	1.5mm x 7mm
Magnetically treated for	EHD-P3	0.5mm x 1mm	EHD-S7	1.0mm x 5mm	EHD-P43	1.5mm x 10mm
enhanced effectiveness	EHD-P4	0.5mm x 3mm	EHD-A1	1.0mm x 7mm	EHD-S10	2.0mm x 5mm

EHD-P41

0.5mm x 5mm

USAGE TIPS:

• For hard materials and increase power - Use media 0.5mm diameter or larger

EHD-S4

- For softer materials Use 0.5mm diameter media or smaller
- Use 3mm length media for parts with small holes and crevices
- Always use media with diameters smaller than the holes of your parts



1.0mm x 10mm

660 Parts & Media Separator



PFS-747 1-gallon PFS-7475G 5-gallon

